

Properties	2050 SB-19	2052 SB-19	2952 SB
Continuous scale	●	●	●
Shock proof	●	●	●
Damped endpoint	●	●	●
Jewel bearing	●	●	●
Scale graduation counterclockwise			●

Analogue Dial Indicators

Series 2

Standard size with 0.01 mm graduation



Specifications

Accuracy: Factory specification / DIN
Delivered with factory certificate

Notation "B" = without eyelet

For various accessories see pages 206 and 207.
For special measuring inserts see pages 208 and 209.



No. 2050 SB-19 in stand no. 7002 M

Measuring range mm	Graduation mm	No.	Scale	1 Pointer rotation mm	f_e μm	f_{ges} μm	f_u μm	Measuring force max. N	Mass g	Note
20	0,01	2050 SB-19	0-100 (100-0)	1	25	30	4	2,0	140	☑ ☑ ☑ ☑
30	0,01	2052 SB-19	0-100 (100-0)	1	30	35	4	2,5	143	☑ ☑ ☑
30	0,01	2952 SB	100-0	1	30	35	4	2,5	143	☑ ☑ ☑

No. without "B" Δ Lid with eyelet supplied

No.	A mm	B mm	C mm	D mm	F mm	G mm	H mm	I mm
2050 SB-19	38,8	75,2	57	17,7	16,9	29,8	52	7,6
2052 SB-19	38,8	88,7	57	17,7	16,9	43,3	52	7,6
2952 SB	38,8	88,7	57	17,7	16,9	43,3	52	7,6

