



Digital-Multimeter, 3 1/2-digit

Steady performance digital-multimeter, which provides an overload protection and the functions of measuring like DCV, ACV, DCA, ACA, resistance, capacitance, frequency, diode, continuity test with buzzer and temperature; ideal for the education- and service-fields.

- ▶ 28 mm, 3 1/2-dgt. LCD display with backlight, max. 2000
- ▶ manual range selection, low battery indication
- ▶ hFE-Test, Peak-Hold
- ▶ with 200 mA automatic circuit breaker
- ▶ Auto power off
- ▶ Safety: IEC-1010-1; CAT II 1000 V
- ▶ 200 mA automatic circuit breaker
- ▶ Accessories: holster, carrying case, test leads, typ-K- thermocouple probe, battery and manual

DCV	200 mV/2/20/200/1000 V; 100 μ V; \pm 0,5 % + 3 dgt.
ACV	200 mV/2/20/200/750 V; 100 μ V; \pm 0,8 % + 5 dgt. Freq.-range: 40 ... 400 Hz
DCA	2/20/200 mA/20 A; 1 μ A; \pm 0,8 % + 3 dgt.
ACA	2/20/200 mA/20 A; 1 μ A; \pm 1,0 % + 5 dgt. Freq.-range: 40 ... 200 Hz
Ohm	200 Ω /2/20/200 k Ω /2/20/2000 M Ω ; 0,1 Ω ; \pm 0,8 % + 3 dgt.
Cap.	20/200 nF/2/20/200 μ F; 10 pF; \pm 2,5 % + 20 dgt.
Induct.	2/20/200 mH/2/20 H; 1 μ H; \pm 2,5 % + 20 dgt.
Freq.	2/20/200/2000 kHz/10 MHz; 1 Hz; \pm 0,5 % + 4 dgt.
Temp.	-40 ... +1000°C; 1°C; \pm 1,0 % + 4 dgt.
Operation Voltage	9 V-battery
Dimensions (WxHxD)	100 x 190 x 35 mm
Weight	400 g