

productphoto



product details

Article No. P 2015

Digital-Multimeter

Steady performance digital-multimeter, which provides an overload protection and the functions of measuring like MIN/MAX, REL, duty cycle, DCV, ACV, DCA, ACA, resistance, capacitance, frequency, diode, continuity test with buzzer and temperature; ideal for the education- and service-fields.

- ▶ 23 mm, 3 3/4-digit LCD display, max. 4000
- ▶ auto ranging or manual range selection
- ▶ low battery indication
- ▶ Auto power off
- ▶ Safety: IEC-1010-1; CAT II 1000 V
- ▶ Accessories: holster, carrying case, test leads, typ-K- thermocouple probe, battery and manual

DCV	400 mV/4/40/400/1000 V; 100 µV; ± 0,5 % + 6 dgt.
ACV	400 mV/4/40/400/750 V; 100 µV; ± 0,8 % + 6 dgt.; Freq.-range: 40 ... 400 Hz
DCA	400/4000 µA/40/400 mA/20 A; 0,1 µA; ± 1,0 % + 5 dgt.
ACA	400/4000 µA/40/400 mA/20 A; 0,1 µA; ± 1,5 % + 5 dgt.; Freq.-range: 40 ... 200 Hz
Ohm	400 Ω/4/40/400 kΩ/4/40 MΩ; 0,1 Ω; ± 0,8 % + 4 dgt.
Cap.	40/400 nF/4/40/400 µF; 1 pF; ± 2,5 % + 6 dgt.
Freq.	100/1000 Hz/10/100 kHz/1/30 MHz; 0,1 Hz; ± 0,5 % + 4 dgt.
Temp.	-40 ... +1000°C; 1°C; ± 1,0 % + 4 dgt.
Operation Voltage	9 V-battery
Dimensions (WxHxD)	100 x 190 x 35 mm
Weight	400 g