

PeakTech® 2700

Prod-Id: P 2700



Earth Resistance Tester, 3 1/2-digit

Electronic Digital Earth Resistance Tester designed for measurement of the resistance of earthing used in the electrical equipment as well as for measurement of ground resistivity. It can be used for measurements of the other low regular, liquid resistances, voltage AC, voltage DC and electrical resistance. This Earth Resistance Tester finds wide application for testing earthing installation in power based industries, telecommunication networks and electrical traction systems, etc.

- dual 3 1/2 digit LCD display (max.2000) with backlight
- automatic zero adjustment
- auto power off
- Low battery and overrange indication; data hold
- Safety: EN-61010-1; CAT III 1000 V
- Accessories: carrying case, test leads red 15 m, yellow 10 m, green 5 m, 2 pcs. earth spikes, batteries and manual

earth voltage	200 V; 0,1 V; $\pm 3,0\%$ + 3 dgt.
earth ranges	20/200/2000 Ω $\pm 2,0\%$ + 3 dgt.
DC voltage range	1000 V; 1 V; $\pm 0,8\%$ + 3 dgt.
AC voltage range	750 V; 1 V; $\pm 1,2\%$ + 10 dgt.
resistance	200 k Ω ; 0,1 k Ω ; $\pm 1,0\%$ + 2 dgt.
operation voltage	6 x 1,5 V AA (UM-3) batteries
dimensions (WxHxD)	92 x 200 x 50 mm
weight	700 g